

## REVERBERATION CHAMBER



The heart of the acoustic laboratory is the reverberation chambers, which have been specially built and decoupled from wall or ceiling slabs for the purpose of acoustic measurement. The chamber volumes are 175m<sup>3</sup> and 265m<sup>3</sup>. Depending on the measuring task, the tests are carried out in the respective antechambers or in the reverberation chamber itself. All the walls of the reverberation chambers are acoustically hard and antiparallel, which enables a good distribution of sound in the chamber. In this diffuse sound field – above a certain limiting frequency and within a standard tolerance range – identical sound pressure levels are measured at measurement points that are freely selected. The sound pressure levels measured are converted into sound output values. These form the basis for the acoustic data in our product documentation.

### TROX España

---



Ctra. Castellón, Km. 7  
Pol. Ind. La Cartuja  
E-50720 Zaragoza  
Tel: +34 976 50 02 50  
Fax + 34 976 50 09 04  
Email: [trox@trox.es](mailto:trox@trox.es)

### Servicios myTROX

---

- > [Contactos](#)

---

- > [Formulario de contacto](#)

---

- > [Mapa de situación](#)

---

- > [Condiciones de venta y garantía](#)

---

- > [TROX Plazos de entrega](#)

---

- > [Certificado AENOR](#)

---

- > [Certificado IQNet](#)

---

- > [Certificado TÜV](#)

---

### Contacto telefónico:

---

Delegaciones comerciales  
[Contacto](#)

Customer Service  
+34 976 50 02 50

Horario de atención al cliente: de Lunes a  
Jueves de 9:00 a 14:00 y de 15:30 a 17:30 ·  
Viernes de 9:00 a 14:00 h

### TROX EN REDES SOCIALES

---